25X1

## INFORMATION REPORT INFORMATION REPORT

## CENTRAL INTELLIGENCE AGENCY

25X1

This material contains information affecting the National Defense of the United States within the meaning of the Espionage Laws, Title 18, U.S.C. Secs. 793 and 794, the transmission or revelation of which in any manner to an unauthorized person is prohibited by law.

COUNTRY	USSR (Khabarovsk Kray)	REPORT
SUBJECT	Gold Mines at imeni Matrosova	DATE DISTR. 9 March 1955 25X1
		NO. OF PAGES · #
DATE OF INFO.		REQUIREMENT
PLACE ACQUIRED		REFERENCES
DATE ACQUIRED		
	SOURCE EVALUATIONS ARE DEFINITIVE. APPR	AISAL OF CONTENT IS TENTATIVE
		AND SI CONTENT IS TENTALLY


- 1. There were four gold mines at imeni Matrosova (N 61-39, E 147-51) (rudnik imeni Matrosova): Mines No. 1 and No. 2 were horizontal, dug straight into the mountain; Mine No. 3 was vertical, 100 meters below the surface; and Mine No. 4 was 150 meters deep. One tunnel from Mine No. 3 went under Mine No. 1, and 25X1 there was a skip which brought the ore from Mine No. 3 out through Mine No. 1.
- 2. Mine No. 1 consisted of a horizontal tunnel which went some 200 meters into the mountainside. After the first 100 meters, there was a division, one tunnel being 60 meters deep, the other 100 meters. At the face, a power 25X1 drill was used to dig holes about 80 centimeters deep and then dynamite was used to blow up the work. At the far end of the face (zaboy), there was a chain conveyor with buckets to carry the ore to the mine railroad, which had small dump cars. The ore dropped into the cars, and when they were loaded the cars were pushed by hand to the outside. There, the ore was loaded onto trucks by same kind of winch or loading device (lebedka) and taken to a concentration factory in Beriya (N 61-40, E 147-55), about five kilometers away. The norm for one man was 120 carloads in eight hours when he worked near the conveyor. A man usually did only 60 carloads and, even when the prisoners were kept up to nine and ten hours, they managed no more than 80 carloads. At some faces, they had to work by hand, using shovels to fill the cars instead of a conveyor. By hand, it took one hour to load a car. In some other places, two men worked together making the ore fall from overhead down into wheelbarrows. This type of mining produced about one ton per day. Where the men had to dig and load, the norm was 2.5 to 3 cubic meters per man per shift. A man usually made only 1.5 to 2 cubic meters. About 80 trucks were available for moving the ore to the factory. At any one time, there would be five to 20 trucks being loaded.
- 3. Mine No. 3 was much larger than Mine No. 1. In 1951, an electric railway was installed in this mine. The mine had a vertical shaft, 100 meters deep,

							•			_	J				
STATE	Х	ARMY	x	NAVY	x	AIR	x	FBI	AEC		189	EV X	,	$\neg$	
							(Note:	Washingto	n distribution				d distribution	on by	"#".)

25X1

25X1

				25X
		-2-		
	skip for the ore 1 to 1.5 tons. the faces. Afte the faces. One kilometers long, capacity, took u subdivided into finally there wa most of them with which carried the tunnel had a car Two generators in the skip. From the skip. From the skip. From the skip together they profit to the skip together they profit together they prof	wit about six to eight meters in diameter and apacity of 30 tons. An elevator (klet) for were installed in the shaft. The skip had From the pit, a main tunnel, 700 meters long r some 30 meters, one shaft led away from the of these was 150 meters long; another, one a led under Mine No. 1, where a smaller skip, p the ore. The shaft, which was 150 meters lessmaller shafts, which again led to smaller distributed in the smaller of the smaller of the sum of the smaller. In this mine, there were man are ore to the three electric trains. The trained are capacity of 500 kilograms. The other two contents the sum of the mine furnished the power. The trains of the mine furnished the power. The trains of the mine furnished the power working in the sum of the sum	the workers and a a load capacity of in 1951, led to e mine tunnel toward nd a half to two of one-half-ton ong, was further iggings, until ccupied in digging, y chain conveyors in in the 700-meter ould hold 1.5 tons. brought the ore to 25X1 emptied into the ok the ore to the this mine. and produced 800 to	25X
4.	12 large milling hood and processe Beriya factory wa one of the larges	ported by the overhead conveyor to a large of itelnaya fabrika imeni Beriya). This factor machines. It also received ore from other m d a total of more than 1,500 tons of ore per s larger than the one in Belovol; t of its kind in the Kolyma region. e varied between three and 16 percent. The old.	y was equipped with ines in the neighbor- 12-hour day. The in fact, it was	25X <sup>2</sup>
5.	number of difficulties with the air composite of the comp	tion was smaller than in the other seasons of e mines during December, January, and Februar lties in that season: shortage of electric of ressors and the water. The factory at Beriya these three winter months.	ry because of a	
6.	Matrosova started	using forced labor in 1948.		
7.	There were several prospectors (razve veyed the land for	l abandoned mines in the region, but there we dochnaya brigada), made up of some 18 free we mines.	as also a group of workers who sur-	
8.	Until about 1948-1 search of gold nug but no money for t	949, prisoners with light sentences were all gets. They had to turn the muggets in and rhis gold.	owed to roam in received extra food	
9.	mine railroad (mot had no electric po built there in 195	gns of modernization and mechanization. Eve 951, no machinery was used in Mine No. 1. A ovoz) was built in Mines No. 1 and No. 4. U wer. An electric train (elektrovoz) with the long conveyor from Matrosova to the ning equipment was of very diverse origins;	t that time, the ntil 1949, Mine No. 3	25X <sup>2</sup>
		Offen De		
		, SECRET		25X



electric railway (elektrovoz)

